

Table 1: Build and lift heights of duplex lift mast with swivel fork, Supplementary lift 1.700 mm or 2.300 mm

Total lift height with 1.700 mm suppl. lift	Total lift height with 2.300 mm suppl. lift	Cabin lift height	Raised platform height	Extended height cabin**	Closed height EK 1100 to 1300 two-stage-mast*	Closed height EK 1350/1500 two-stage-mast*	Closed height EK 1500 XL two-stage-mast	Closed height EK 2000 two-stage-mast***
h3G + s	h3G + s	h3 + s	h12	h6	h1	h1	h1	h1
mm	mm	mm	mm	mm	mm	mm	mm	mm
4.200	4.800	2.500	2.820	4.820	2.495	-	-	-
4.700	5.300	3.000	3.320	5.320	2.745	-	-	-
5.200	5.800	3.500	3.820	5.820	2.995	2.920	-	3.170
5.700	6.300	4.000	4.320	6.320	3.245	3.170	-	3.420
6.200	6.800	4.500	4.820	6.820	3.495	3.420	-	3.670
6.700	7.300	5.000	5.320	7.320	3.745	3.670	-	3.920
7.200	7.800	5.500	5.820	7.820	3.995	3.920	-	4.170
7.700	8.300	6.000	6.320	8.320	4.245	4.170	-	4.420
8.200	8.800	6.500	6.820	8.820	4.495	4.420	-	4.670
8.700	9.300	7.000	7.320	9.320	4.745	4.670	-	4.920
9.200	9.800	7.500	7.820	9.820	4.995	4.920	-	5.170
9.700	10.300	8.000	8.320	10.320	5.245	5.170	-	5.420
10.200	10.800	8.500	8.820	10.820	-	5.420	-	5.670
10.700	11.300	9.000	9.320	11.320	-	5.670	-	5.920
11.200	11.800	9.500	9.820	11.820	-	5.920	-	6.170
11.700	12.300	10.000	10.320	12.320	-	6.170	-	6.420
12.200	12.800	10.500	10.820	12.820	-	6.420	-	6.670
12.700	13.300	11.000	11.320	13.320	-	6.670	-	6.920
13.200	13.800	11.500	11.820	13.820	-	6.920	-	7.170
13.700	14.300	12.000	12.320	14.320	-	7.170	7.420	-
14.200	14.800	12.500	12.820	14.820	-	-	7.670	-
14.700	15.300	13.000	13.320	15.320	-	-	7.920	-
15.200	15.800	13.500	13.820	15.820	-	-	8.170	-
15.700	16.300	14.000	14.320	16.320	-	-	8.420	-

*EK 1100 maximum closed height 4.745 mm; *EK 1350 maximum closed height 6.170 mm; other closed/lift heights on request.

Extended height with 2.300 mm suppl. lift + 600 mm; *EK 2000 reduced total lift heights, supplementary lift = 1.500 mm; other heights on request.

Table 2: Build and lift heights of triplex lift mast with swivel fork, Supplementary lift 1.700 mm or 2.300 mm

Total lift height with 1700 mm suppl. lift	Total lift height with 2300 mm suppl. lift	Cabin lift height	Raised platform height	Extended height cabin**	Closed height EK 1100 to 1300 three-stage-mast*	Closed height EK 1350/1500 three-stage-mast	Closed height EK 1500 XL three-stage-mast
h3G + s	h3G + s	h3 + s	h6	h6	h1	h1	h1
mm	mm	mm	mm	mm	mm	mm	mm
5.450	6.050	3.750	4.070	6.070	2.495	-	-
6.200	6.800	4.500	4.820	6.820	2.745	-	-
6.950	7.550	5.250	5.570	7.570	2.995	2.920	-
7.700	8.300	6.000	6.320	8.320	3.245	3.170	-
8.450	9.050	6.750	7.070	9.070	3.495	3.420	-
9.200	9.800	7.500	7.820	9.820	3.745	3.670	-
9.950	10.550	8.250	8.570	10.570	3.995	3.920	-
10.700	11.300	9.000	9.320	11.320	-	4.170	-
11.450	12.050	9.750	10.070	12.070	-	4.420	-
12.200	12.800	10.500	10.820	12.820	-	4.670	4.920
12.950	13.550	11.250	11.570	13.570	-	4.920	5.170
13.700	14.300	12.000	12.320	14.320	-	5.170	5.420
14.450	15.050	12.750	13.070	15.070	-	5.420	5.670
15.200	15.800	13.500	13.820	15.820	-	-	5.920
15.950	16.550	14.250	14.570	16.570	-	-	6.170

*EK 1100 maximum closed height 3.495 mm; ** extended height with 2.300 mm suppl. lift + 600 mm; other closed/lift heights on request.

The overall length with triplex mast: EK 1100/1200/1300 is 35 mm longer; EK 1350/1500 is 125 mm longer; EK 1350 closed height > 4.170 mm same length as EK 1500.

Table 3: Aisle width depending on load/pallet dimensions

Load dimension		Distance between loads**	Boom length	EK 1100 Transfer aisle width*	EK 1200/1300 Transfer aisle width*	EK 1350 Transfer aisle width*	EK 1500/2000 Transfer aisle width*
depth	width						
b	d	Ast	M1S	mm	mm	mm	mm
mm	mm	mm	mm	mm	mm	mm	mm
1.240	835	1.700	460	3.480	3.530	3.570	3.820
1.200	800	1.650	460	3.460	3.510	3.550	3.800
1.200	1.000	1.650	550	3.540	3.600	3.630	3.890
1.200	1.200	1.650	650	3.630	3.690	3.720	3.980
1.000	800	1.450	460	3.380	3.440	3.470	3.730
1.000	1.000	1.450	550	3.460	3.520	3.560	3.820
1.000	1.200	1.450	650	3.560	3.610	3.650	3.910
800	800	1.400	460	3.360	3.420	3.460	3.710
800	1.000	1.400	550	3.450	3.500	3.540	3.800
800	1.200	1.400	650	3.540	3.600	3.630	3.900
835	1.240	1.400	650	3.540	3.600	3.630	3.900

*Transfer aisle width without load and 580 mm fork carriage width, with mechanical guidance + 300 mm, with wire guidance + 800 mm recommended. Aisle width for mechanical guidance and duplex mast; Reduced truck lengths on request. ** EK 2000 + 50 mm

ORDER PICKING and narrow aisle truck




Technical Data
DC-TECHNOLOGY



ORDER PICKING AND NARROW AISLE TRUCK WITH SEM-TECHNOLOGY

EK 1100 EK 1200 EK 1300 EK 1350 EK 1500 EK 1500 XL EK 2000

Load capacity	Q	1.100 kg	1.200 kg	1.300 kg	1.350 kg	1.500 kg	1.500 kg	2.000 kg
Load centre	C	600 mm	600 mm	600 mm	600 mm	600 mm	600 mm	600 mm
Power supply		Electrical	Electrical	Electrical	Electrical	Electrical	Electrical	Electrical
Operator type		Stand-on/Rider seated	Stand-on/Rider seated	Stand-on/Rider seated	Stand-on/Rider seated	Stand-on/Rider seated	Stand-on/Rider seated	Stand-on/Rider seated
Tyres		Polyurethan	Polyurethan	Polyurethan	Polyurethan	Polyurethan	Polyurethan	Polyurethan
Number of wheels, drive/load side (x = driven)		1x/2	1x/2	1x/2	1x/2	1x/2	1x/2	1x/2
Driver`s cabin height	h8	400 mm	400 mm	400 mm	400 mm	400 mm	400 mm	400 mm
Lift height	h3G+s	see table	see table	see table	see table	see table	see table	see table
Supplementary lift	h2	1.700 mm	1.700 mm	1.700 mm	1.700 mm	1.700 mm	1.700 mm	1.500 mm
Picking height	h9	h6 - 400 mm	h6 - 400 mm	h6 - 400 mm	h6 - 400 mm	h6 - 400 mm	h6 - 400 mm	h6 - 400 mm
Fork dimensions		40/120 mm	40/120 mm	40/120 mm	40/120 mm	40/120 mm	40/120 mm	40/120 mm
Fork length		800 - 1.300 mm	800 - 1.300 mm	800 - 1.300 mm	800 - 1.300 mm	800 - 1.300 mm	800 - 1.300 mm	800 - 1.300 mm
Width across forks	B3	505 - 795 mm	505 - 795 mm	505 - 795 mm	505 - 795 mm	505 - 795 mm	505 - 795 mm	240 - 795 mm
Height of fork, low position	s	80 mm	80 mm	80 mm	80 mm	80 mm	80 mm	80 mm
Overall length with fork carrier width 850 mm	L	3.275 - 3.365 - 3.465 mm	3.335 - 3.425 - 3.525 mm	3.335 - 3.425 - 3.525 mm	3.375 - 3.465 - 3.565 mm	3.650 - 3.740 - 3.840 mm	3.650 - 3.740 - 3.840 mm	3.740 - 3.840 mm
Overall length with fork carrier width 580 mm	L	3.140 - 3.230 - 3.330 mm	3.200 - 3.290 - 3.390 mm	3.200 - 3.290 - 3.390 mm	3.240 - 3.330 - 3.430 mm	3.515 - 3.605 - 3.705 mm	3.515 - 3.605 - 3.705 mm	3.605 - 3.705 mm
Support boom length (standard)	M1S	460 - 550 - 650 mm	460 - 550 - 650 mm	460 - 550 - 650 mm	460 - 550 - 650 mm	460 - 550 - 650 mm	460 - 550 - 650 mm	550 - 650 mm
Overhang	X/X1	355/255 mm	355/255 mm	355/255 mm	365/255 mm	360/270 mm	360/270 mm	360/270 mm
Overall width	B	1.000 - 1.700 mm	1.200 - 1.700 mm	1.200 - 1.700 mm	1.200 - 1.700 mm	1.200 - 1.700 mm	1.200 - 1.700 mm	1200 - 1.700 mm
Height of mast retracted	h1	see table	see table	see table	see table	see table	see table	see table
Height of cabin extended	h6	see table	see table	see table	see table	see table	see table	see table
Height of mast extended	h4	see table	see table	see table	see table	see table	see table	see table
Turning radius	Wa	2.080 mm	2.140 mm	2.140 mm	2.170 mm	2.445 mm	2.445 mm	2.445 mm
Aisle width	Ast	1.200 - 2.000 mm	1.400 - 2.000 mm	1.400 - 2.000 mm	1.400 - 2.000 mm	1.400 - 2.000 mm	1.400 - 2.000 mm	1.400 - 2.000 mm
Travel speed laden/unladen		10,0/10,0 km/h	10,0/10,0 km/h	10,0/10,0 km/h	10,0/10,0 km/h	10,0/10,0 km/h	10,0/10,0 km/h	10,0/10,0 km/h
Lift speed laden/unladen		0,23/0,26 m/s*	0,31/0,37 m/s*	0,30/0,37 m/s*	0,37/0,45 m/s*	0,36/0,45 m/s*	0,42/0,45 m/s*	0,32/0,42 m/s*
Lowering speed laden/unladen		0,45/0,45 m/s	0,45/0,45 m/s	0,45/0,45 m/s	0,45/0,45 m/s	0,45/0,45 m/s	0,45/0,45 m/s	0,45/0,45 m/s
Reach speed laden/unladen (adjustable)		0,20/0,20 m/s****	0,20/0,20 m/s****	0,20/0,20 m/s****	0,20/0,20 m/s****	0,20/0,20 m/s****	0,20/0,20 m/s****	0,20/0,20 m/s****
Weight including battery		4.900 - 5.900 kg	4.900 - 6.300 kg	5.000 - 6.400 kg	5.800 - 6.900 kg	7.400 - 8.300 kg	8.200 - 8.900 kg	7.400 - 8.800 kg
Axle load with load, drive side/load side		1.600/4.400; 1.900/5.100 kg	1.600/4.500; 2.000/5.500 kg	1.650/4.550; 2.050/5.600 kg	1.800/5.300; 2.050/6.150 kg	2.490/6.410; 2.745/7.055 kg	2.720/6.980; 2.910/7.490 kg	2.150/7.250; 2.550/8.250 kg
Axle load without load, drive side/load side		2.100/2.800; 2.400/3.500 kg	2.100/2.800; 2.500/3.800 kg	2.150/2.850; 2.550/3.850 kg	2.400/3.400; 2.700/4.200 kg	2.995/4.405; 3.360/4.940 kg	3.280/5.020; 3.560/5.340 kg	3.000/4.400; 3.400/5.400 kg
Tyres, number, drive side/load side		1/2	1/2	1/2	1/2	1/2	1/2	1/2
Tyres dimension drive side		343/140 mm	343/140 mm	343/140 mm	343/140 mm	381/152 mm	381/152 mm	381/152 mm
Tyres dimension load side		343/140 mm	343/140 mm	343/140 mm	377/178 mm	377/178 mm	377/178 mm	377/178 mm
Wheel base	y	1.780 mm	1.840 mm	1.840 mm	1.880 mm	2.140 mm	2.140 mm	2.140 mm
Ground clearance	m2	40 mm	40 mm	40 mm	40 mm	40 mm	40 mm	40 mm
Operating brake		electro-magnetic	electro-magnetic	electro-magnetic	electro-magnetic	electro-magnetic	electro-magnetic	electro-magnetic
Parking brake		dead man`s brake	dead man`s brake	dead man`s brake	dead man`s brake	dead man`s brake	dead man`s brake	dead man`s brake
Battery		DIN 43531 B	DIN 43531 B	DIN 43531 B	DIN 43536 A	DIN 43536 A	DIN 43536 A	DIN 43536 A
Battery voltage/capacity		48 Volt/775 Ah**/**	48 Volt/930 Ah**/**	48 Volt/930 Ah**/**	80 Volt/465 Ah***	80 Volt/775 Ah***	80 Volt/775 Ah***	80 Volt/775 Ah***
Battery weight		1.118 kg	1.309 kg	1.309 kg	1.238 kg	1.862 kg	1.862 kg	1.862 kg
Drive motor		5,0 kW	5,0 kW	5,0 kW	5,0 kW	5,0 kW	5,0 kW	5,0 kW
Lift motor		10,0 kW*	12,0 kW*	12,0 kW*	21,0 kW*	21,0 kW*	26,0 kW	21,0 kW*
Drive/lift control		electr.Tr.-pulses./infinitely var.	electr.Tr.-pulses./infinitely var.	electr.Tr.-pulses./infinitely var.	electr.Tr.-pulses./infinitely var.	electr.Tr.-pulses./infinitely var.	electr.Tr.-pulses./infinitely var.	electr.Tr.-pulses./infinitely var.



*Higher lift speeds on request, **also in 80 Volt available, ***other capacities on request, **** up to 0,45 m/s on request.